

In the Claims:

Please amend claim 36.

Please withdraw claims 37-42 and 50-55 from consideration.

All pending claims have been reproduced below for the Examiner's convenience.

Sub  
E1  
Barrow's

1. A surgical fastener comprising:  
a base having at least one substantially planar surface,  
a flange bendably joined to a first edge of the base and having at least one substantially planar surface adapted to cooperate with the planar surface of the base,  
a pin bendably joined to the base at a second edge of said base opposing the first edge, and  
a needle for skewering tissues, or tissue and graft, the needle being removably joined to the pin to receive the tissues, or tissue and graft, from the needle, the pin and flange capable of bending over the base to fix the tissues, or tissue and graft, together.

E

B

2. A surgical fastener defined in claim 1 wherein the base is configured to be releasably engaged with an associated applying instrument.

3. A surgical fastener for securing portions of tissues, or tissue and graft, together comprising:

base means having at least one substantially planar surface,  
flange means bendably joined to a first edge of the base means and having at least one substantially planar surface for cooperating with the planar surface of the base means,

pin means bendably joined to the base means at a second edge of said base opposing the first edge, and

needle means removably joined to the pin means for piercing tissues, or tissue and graft, wherein the base means and the flange means each have cooperating surfaces to contact and secure on the pin means portions of tissues, or tissue and graft, to be joined together.

4. A surgical fastener defined in claim 3 wherein the base means includes means for releasably engaging an associated applying instrument.

5. An instrument for applying a surgical staple comprising:  
an elongated shaft having a distal end portion,  
a staple holder at the distal end portion adapted to engage a staple and a needle removably joined to the staple, the staple having a base including at least one substantially planar surface, a flange bendably joined to a first edge of the base and having at least one substantially planar surface adapted to cooperate with the planar surface of the base, and a pin bendably joined to an edge of the base opposing said first edge,

a staple forming member at the distal end portion adapted to bend the pin over a substantial portion of the base and to bend the flange over a substantial portion of the pin, so that the staple is substantially closed, and

a handle having a control for actuating the staple forming member.

M 6. An instrument defined in claim 5 wherein the elongated shaft has a length and width adapted for use in minimally invasive surgery.

M 7. An instrument as defined in claim 5 wherein the base is configured to be releasably engaged by the staple holder, and the handle has a control for releasing the staple after it is closed.

M 8. An instrument as defined in claim 5 wherein the staple holder is also adapted to articulate the needle relative to the elongated shaft, and the handle has a control for actuating an articulating mechanism.

CI 9. An instrument as defined in claim 5 wherein the instrument further comprises a needle removal member at the distal end portion adapted to remove the needle from the staple.

M 10. An instrument as defined in claim 5 wherein:  
the base and the flange each have cooperating surfaces to contact and secure on the pin portions of tissues to be joined or portions of a graft to an artery.

M 11. An instrument as defined in claim 10 wherein the elongated shaft has a maximum diameter less than about 20 millimeters.

5  
Sub  
E3  
M

12. An instrument for applying a surgical staple comprising:

an elongated shaft having a distal end portion,

staple holder means at the distal end portion for holding a staple and a needle

removably attached to the staple for piercing tissues, or tissue and graft, the staple comprising base means having at least one substantially planar surface for securing tissues or grafts, flange means bendably joined to one edge of the base means and having at least one substantially planar surface for cooperating with the planar surface of the base means to secure tissues or grafts, and pin means bendably joined to the base means at an opposing edge for holding tissues or grafts, wherein the base means and the flange means each have cooperating surfaces to contact and secure on the pin means portions of tissues to be joined together or portions of a graft to an artery,

C

staple forming means associated with the staple holder means for bending the pin means over a portion of the base means, and for folding the flange means over a substantial portion of the pin means so that the staple is substantially closed, and

L

a handle having control means for actuating the staple forming means.

13. An instrument defined in claim 12 wherein the elongated shaft has a length and width adapted for use in minimally invasive surgery.

14. An instrument as defined in claim 12 wherein the base means includes means for releasably engaging the staple holder means, and the handle has control means for releasing the staple after it is closed.

M 15. An instrument as defined in claim 12 wherein the staple holder means includes means to articulate the needle relative to the elongated shaft, and the handle has control means for actuating such articulation means.

C1 16. An instrument as defined in claim 12 wherein the instrument further comprises needle removal means at the distal end portion for removing the needle from the pin means.

M 17 18. An instrument as defined in claim 12 wherein the elongated shaft has a maximum diameter less than about 20 millimeters.

M 18 19. A method for attaching soft tissues located in the abdominal cavity, chest and retroperitoneal space and for attaching a graft to an artery in these areas comprising:

M providing an instrument for applying a surgical staple having an elongated shaft with a distal end portion and having a staple forming member at the distal end portion adapted to bend portions of a staple,

C2 providing a staple holder at the distal end of the instrument with at least one staple, and a needle attached to each at least one staple, the at least one staple comprising a base having at least one substantially planar surface, a flange bendably joined to one edge of the base and having at least one substantially planar surface adapted to cooperate with the planar surface of the base, and a pin bendably joined to the base at an opposing edge, wherein the base and the flange each have cooperating surfaces to contact and secure on the pin portions of tissues to be joined together or portions of a graft to an artery,

incising a patient's tissue to create at least one opening into the patient's abdominal cavity, chest or retroperitoneal space,

inserting the distal end of the instrument through the opening, so that the distal end is disposed in the patient,

C<sup>2</sup> passing the needle through a portion of one tissue, graft or artery and through a portion of a second tissue, artery or graft, and

actuating the staple forming member to bend the pin over a substantial portion of the base and to bend the flange over a substantial portion of the pin, so that the staple is substantially closed.

19 21. The method defined in claim 19 wherein the passing and actuating steps are repeated to apply additional staples. 18

C<sup>3</sup> 20 22. The method defined in claim 19 wherein the incising step creates a small incision and wherein the inserting, passing and actuating steps are performed by minimally invasive surgical procedures. 18

21 23. The method defined in claim 19 wherein the shaft of the needle is passed through a portion of a first graft or artery and through a second artery or graft to form a portion of an artery to graft anastomosis. 18

Sub 51  
26. A surgical staple system for fastening together tissues, or tissue and graft, comprising:

3  
a first section adapted to be removably joined to a tissue and/or graft piercing implement; and

2  
a second section adjacent to said first section and adapted to be releasably gripped by a staple applying instrument, said first and second sections capable of moving from a first orientation, where portions of said first and second sections are spaced apart sufficiently to receive the tissues, or tissue and graft, therebetween, to a second orientation, where said first and second sections lie in contact with the tissues, or tissue and graft.

CC  
27. A surgical staple as recited in claim 26, further comprising a third section adjacent to said second section, said third section capable of being bent with respect to said second section.

28. A surgical staple as recited in claim 26, further comprising a piercing implement removably joined to said first section.

Sub 52  
29. A surgical staple system for fastening tissues, or tissue and graft, together, comprising:

a base having a substantially planar surface and adapted to be releasably gripped by a staple applying instrument;

a flange having a substantially planar surface attached to a first edge of said base, said flange capable of moving from a first position, where said substantially planar

surfaces of said flange and base are spaced apart sufficiently to receive the tissues, or tissue and graft, therebetween, to a second position, where said substantially planar surfaces of said base and flange lie in contact with the tissues, or tissue and graft; and

a pin attached to a second edge of said base different from said first edge, said pin adapted to releasably join with a needle, said pin capable of moving from a first position, where said pin and said substantially planar surface of said base are spaced apart sufficiently to receive the tissues, or tissue and graft, therebetween, to a second position, where said pin and said substantially planar surface of said base lie in contact with the tissues, or tissue and graft.

25  
30. A surgical staple system as recited in claim 29 further comprising a needle releasably joined to said pin.

24  
31. A surgical staple system for fastening tissues, or tissue and graft, together, comprising:

a staple including at least a first section adjacent to a second section, said first and second sections capable of moving from a first orientation, where said first and second sections are spaced apart sufficiently to receive the tissues, or tissue and graft, therebetween, to a second orientation, where said first and second sections lie in contact with the tissues, or tissue and graft; and

a needle capable of aligning and skewering the tissues, or tissue and graft, said needle removably attached to one of said first or second sections of said staple.



Sub E 6 Sub 3  
CS  
36. (Once Amended) A surgical fastener system, comprising:

a staple including at least first and second joined sections;

a needle affixed adjacent to an end of one section of said at least first and second joined sections;

an instrument capable of manipulating said needle in a minimally invasive procedure such that said needle skewers a first tissue or graft, aligns said first tissue or graft to a desired position with respect to a second tissue or graft, and skewers said second tissue or graft, and said instrument capable of folding said at least first and second joined sections with respect to each other to secure said first tissue or graft to said second tissue or graft between said at least first and second joined sections of the staple.

[37. A surgical staple system comprising:

a staple including first, second and third sections;

a needle affixed to said first section; and

an instrument, including:

a proximal end,

a distal end opposite said proximal end, said distal end including first means for manipulating said needle in a minimally invasive procedure such that said needle skewers tissues, or tissue and graft, onto said first section, and second means for folding said first and third sections with respect to said second section,

means for operatively connecting said proximal and distal ends, and

at least one hand-actuated mechanism in said proximal end for controlling said first means for manipulating said needle and said second means for folding said first and third sections with respect to said second section.]

[38. A surgical staple system as recited in claim 37, further comprising third means in said distal end for removing said needle from said first section.]

[39. A surgical staple system as recited in claim 38, wherein said second means for folding said first and third sections with respect to said second section and said third means for removing said needle from said first section retract proximally from said distal end to provide a clear line of sight for a surgeon to the needle while said first means manipulates said needle.]

[40. A surgical staple system as recited in claim 37, wherein said means for operatively connecting said proximal and distal ends comprises drive rods connected between said hand-actuated mechanisms and said first means for manipulating said needle and said second means for folding said first and third sections with respect to said second section.]

[41. A surgical staple system comprising:  
a staple including first, second and third sections;  
a needle affixed to said first section; and  
an instrument, including:  
a proximal end,

7

a distal end opposite said proximal end, said distal end including first means for manipulating said needle in a minimally invasive procedure such that said needle skewers tissues, or tissue and graft, onto said first section, and second means for folding said first and third sections with respect to said second section,

means for operatively connecting said proximal and distal ends, and

at least one automated robotic mechanism in said proximal end for controlling said first means for manipulating said needle and said second means for folding said first and third sections with respect to said second section.]

[42. A surgical staple system as recited in claim 41, wherein said means for operatively connecting said proximal and distal ends comprises drive rods connected between said automated robotic mechanism and 1) said first means for manipulating said needle, and 2) said second means for folding said first and third sections with respect to said second section.]

43. A surgical staple system for fastening tissues, or tissue and graft, together, comprising:

CG a staple including a first section joined to a second section; and

an instrument having a proximal and distal end, including:

CG means in said distal end for holding said staple,

means in said distal end for articulating said staple,

means in said distal end for bending said first section with respect to said second section in a minimally invasive procedure,

controls located remotely from said distal end for actuating said staple holding means, said staple articulating means, and said bending means, and connecting means for connecting said controls in the proximal end with the staple holding means, said staple articulating means, and said bending means in said distal end.

Sub E2  
44. A surgical staple system as recited in claim 43, further comprising a needle affixed to said staple for skewering the tissues, or tissue and graft, and for locating the tissues, or tissue and graft, in a desired position with respect to the staple.

29  
45. A surgical staple system as recited in claim 44, wherein said needle is articulated by said means for articulating said staple.

30  
46. A surgical staple system as recited in claim 45, further comprising means for removing said needle from said staple.

31  
47. A surgical staple system as recited in claim 46, wherein means for bending said first section with respect to said second section and said means for removing said needle from said staple retract proximally from said distal end to provide a clear line of sight for a surgeon to said needle while said means for articulating said staple articulates said needle.

32  
48. An instrument including distal and proximal ends for fastening tissues, or tissue and graft, together with a staple in a minimally invasive surgical procedure, the staple

including a base, a flange attached to a first edge of said base, and a pin attached to an edge of said base other than the first edge, the pin having a needle removably mounted thereon for skewering the tissues, or tissue and graft, comprising:

a staple holder in the distal end for holding the staple and needle;

means in the distal end for articulating said staple holder, to manipulate the needle such that the needle skewers the tissues, or tissue and graft, on the needle in a desired position with respect to each other, and positions the tissues, or tissue and graft, on the pin;

means in the distal end for removing the needle from the staple;

a staple forming member in the distal end, including:

means for bending the pin down over the base, and

means for bending the flange down over the pin and base;

controls located remotely from said distal end for actuating said means for articulating said staple holder, said means for removing the needle, and said staple forming member; and

connecting means spanning between the distal and proximal ends of the instrument for connecting said controls to said means for articulating said staple holder, said means for removing the needle, and said staple forming member.

33 49. An instrument including distal and proximal ends for fastening tissues, or tissue and graft, together as recited in claim 48, wherein said means for removing the needle from the staple and said staple forming member retract proximally from said distal end to provide a clear line of sight for a surgeon to said needle while said means for articulating said staple holder manipulates said needle. 32

54

50. An instrument including distal and proximal ends for fastening tissues, or tissue and graft, together as recited in claim 48, wherein said controls comprise hand-actuated controls.]

51. An instrument including distal and proximal ends for fastening tissues, or tissue and graft, together as recited in claim 48, wherein said controls comprise automated robotic controls.]

52. An instrument including distal and proximal ends for fastening tissues, or tissue and graft, together as recited in claim 48, wherein said controls and said connecting means together comprise an automated robotic system for actuating said means for articulating said staple holder, said means for removing the needle, and said staple forming member.]

53. An instrument including distal and proximal ends for fastening tissues, or tissue and graft, together as recited in claim 48, further comprising a motor, controlled by said controls, for actuating said connecting means.]

54. An instrument including distal and proximal ends for fastening tissues, or tissue and graft, together as recited in claim 48, further comprising pneumatic means, controlled by said controls, for actuating said connecting means.]

55